

OREGON CORNER RESTORATION FORM

COUNTY: Umatilla. DATE: 03/20/20.

CORNER DESIGNATION: A-21, The Northeast corner of Section 2, Township 1 North, Range 31 East, W.M.

PREVIOUS RENEWALS/SURVEYS ETC: Corner was originally established by Josiah A. Burnett under Contract No. 92 dated September 12, 1860. Notes state: Set post for Cor. To Sec's. 1, 2, 35 and 36, drove charred stake and raised mound with trench as per instructions. John Kimbrell, County Surveyor, in his January, 1909 Survey No. 115, recovered this corner but does not state what was found for the corner. Kimbrell's Survey No. 115 is found in the Record of Private Survey Books.

MONUMENT AND ACCESSORIES FOUND: None. Held fence intersection with fences North and East and old down fence to the South. There are a number of stones on the South side of the held fence intersection but no marks were found on the stones.

MONUMENT MARKING DETAIL:

T2N R31E
S35|S36

S2|S1
· T1N
2020
54657PLS

MONUMENT SET: At the corner position just South of the old fence corner, set a 2 1/2" brass cap on 1 1/4 by 30" galvanized iron pipe 24" in the ground and surrounded with a 3 1/2' diameter mound of earth and stone. Cap is marked as shown in Monument Marking Detail. Nailed a Witness sign to a railroad tie fence post North of the corner monument.

New accessories:

A 5/8 by 24" rebar with blue plastic cap marked "Wells Surveying 54657PLS" bears N 86°21' E, 37.2'.
A 5/8 by 24" rebar with blue plastic cap marked "Wells Surveying 54657PLS" bears N 82°35' E, 15.7'.
A 5/8 by 24" rebar with blue plastic cap marked "Wells Surveying 54657PLS" bears N 84°30' W, 18.1'.
A 5/8 by 24" rebar with blue plastic cap marked "Wells Surveying 54657PLS" bears N 88°03' W, 41.9'.
The rebar accessories are set near fence lines extending from the corner. Wired bearing object signs to each of the rebar accessories.
Bearings to accessories are State Plane Grid bearings.

LOCATION AND COMMENTS:

Corner falls just South of a railroad tie fence corner on an East facing hillside. Fences extend North, East and South.

OREGON STATE PLANE COORDINATE, North Zone NAD 83(91), International Feet Units:

N: 709855.89
E: 8613647.59

FIRM: Wells Surveying
P.O. Box 1696
Pendleton, OR 97801

Surveyor's Seal

\1N31A-21



RENEWS: 6:30:20

20-043-C