ERTIFIED RECORD OF LAND CORNER MONUMENTATION

	E - 11	
History of original corner establishment:	DIAGRAM	
Original corner established by Rufus S. Moore on September 27, 1882, under contract number 451, as follows:	T2S R35E 1/4 <u>S4</u> <u>5</u> 9	
Set a basalt stone $14" \ge 10" \ge 8"$, $10"$ into the ground marked $1/4$ on the west face, from which:	PLS 1636 1995	
A 21" fir bears N32°E, 73 links (48.18 feet). A 3" fir bears S35°W, 62 links (40.92 feet).		_

Description of corner evidence found:

I find a mound of stones at the corner point. One stone is about record size, but has no visible marks, from which:

A 36" Douglas-fir, with scribes visible on a previously opened blaze, bears N32°E, 48.2 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the exact corner point as determined by reference to the remaining original bearing tree, I set a 1" x 30" iron pipe 12" into the ground to bedrock. I build a mound of stones around the pipe to the cap. A 2 1/2" brass cap attached is marked as shown in the diagram above, from which:

A 14" Douglas-fir, scribed "1/4 S9 BT", bears S18°30'E, 106.4 feet. A 9" Douglas-fir, scribed "1/4 S9 BT", bears S48°30'W, 42.1 feet. A 11" Douglas-fir, scribed "1/4 S4 BT", bears N46°30'W, 92.5 feet.

The three new bearing trees are scribed on double blazes, have a 5/8" brass washer, marked "PLS 1636", nailed flush to the lower blaze and have a bearing tree sign nailed above the blazes.

I hereby certify the above corner was perpetuated as hereon described on November 19, 1995. Magnetic declination: 20°E.



Office of the Survey Dept. County of Umatilla for record on the 28. day of Nour mber 1975 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY Utratilla County Surveyor Data 11-95 Roo'd By KK No. 95-209-

