Index N-15	CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No No/4	
T <u>2S</u> R. <u>35E</u> Merid. <u>Willamette</u>	_ R.DLa Grande County_Union No No _ N.F. Wallowa-Whitman_ StoteOregon	
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND	
15 15	A diligent search was made and no evidence or original post or BT's could be found. Area is heavily logged with stumps cut pretty low. Rufus S. Moore blazes his trees approximately 3 - 4 feet above the ground.	
Ž2	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND None.	
PHOTO IDENTIFICATION DATA	5	
Photo No Filed At.		
Object Ident Ident. By	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORN	
PLANE COORDINATE POSITION DATA State Zone	Corner falls in heavily cut area 45 ft. north of E-W fence an cut line and 35 ft. east of N-S dirt road.	
×		

CORNER RECORD (PERPETUATION)

10

n

12

13

Contraction Construction Contraction	INER RECORD (PERPETUAT	
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK Corner position established by propo corners of Section 22. At surveyed pipe with brass cap stamped:	rtioning between the NF	and NW <u>S15</u> nized <u>4</u> S22
Set pipe 24" in ground with mound of		1982 PLS 1099
ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS Bearing Trees: A Tamarack 6" dia. bears N4½°E, 4 A Lodgepole Pine 9" dia. bears S7	49.0 ft scribed $1/4 \text{ s}^2$	15 DT
Work Done By R. Orton Title Part	<u>cy Chief</u> <u>Dote 7/28/82</u>	ote Registration No. Agency
	<u>AL: Union Co. Surveyor's</u>	
Placed wood post 7 ft. west of corner Standard Specifications for Cadastral	. Painted trees and at	tached signs per; 6, Oct., 1979.
Compass Declination: 18½° E	Witnesses: R. Orto G. Wago	n
Placed wood post 7 ft. west of corner Standard Specifications for Cadastral	REMARKS Painted trees and at <u>Surveys</u> , USFS, Region Witnesses: R. Orto	tached signs per 6, Oct., 1979. Mn

Index File No. N-15 T. 2S R. 35E M.Willamette Tract or Surv. No. Cor.