CERTIFIED RECORD OF LAND CORNER MONUMENTATION 1----

T.25. R35E.

14 P

506

DIAGRAM

1

2"P

Restoration of the SE Cor.of Sec.17, T.2 S.R.35 EWM

History of original corner establishment: By Rufus Moore, Sept. 1882

A post 4 ft.long 4 in.sq.24 ins.in ground for cor.to secs. 16,17,20,& 21. 150 ft. above 4 sec.cor. marked. T2SR35E S16 on NE.; T2SR35E S17 on NW; S20 on SW and S21 on SE face with 3 notches on S.and 4 Notches on E.edges from which A fir 22 in.in dia.bears N.54 E. 102 1ks dist.mkd T2SR35E S16BT.

A fir 10 ins.in dia.bears N.52°W 59 lks.dist.mkd T2SR35E SLOBT.

A _ne 22 ins in dia.bears S53°W 53 lks.mkd T2SR35E S20ET A pine 24 ins in dia.bears S19°E 149 lks dist.mkd T2SR35E S21ET

Description of corner evidence found:

Found remains of decayed post, undisturbed in ground. Distances checked from remaining bearing trees. Those bearing trees remaing are: A 22 inch fir snag bears N.54 F.102 lks.dist, scribing visible in old blaze. A 30 inch live pine bears S.19 F 149 lks.dist. scribing visible in old blaze. The two other bearing trees have been destroyed or decayed.

Description of monument and accessories I established to perpetuate the original location of this corner

At the exact corner I set a 1x36 inch galvanized pipe with a 21 inch brass cap securely fastened to the top marked THE REPORT OF CONTRACT

UM	TTT	LL	7 CO01	N.T.X
	SU	RVI	EYOR	
T	2	s.	R.35	Ε.
1.574	s.	17	R.35 S.16	
	s.	20	S.21	
	4.22	190	5.21	
			506	

I burried the rotted piece of post alongside of the pipe and raised a mound of earth 42 ft.base 1 ft.high arround it.From which bear the new Bearing trees.

A **Pine** 14 in.in dia.S.54⁰38'E a dist.of 7.74 ft.mkd T.2SR35S21 CSET A pine 12 in.in dia.S.44⁰20'W.a dist.of 46.40 ft.mkd.T2SR35ES20 CSET A fir 11 in.in dia.N.44⁰25'W. a dist of 12.00 ft.mkd.T2SR35ES17 CSET A fir 6 in.in dia. N.44⁵1'E. a dist.of 62.15 ft.mkd. T2SR35ES16 CSET All angular and linear measurments were taken to the center of the bearing trees with steel tare and Wild T-2 theodolite trees with steel tape and Wild T-2 theodolite.

Office of The Coun State of Oregon	, I hereby certify	County of Umatilla y that the within instrument was filed , 19.68, at o'clock	i in this office m., (signed)
icounty of	FICIAL)	(DEPUTY)	REGISTERED OREGON LAND SURVEYOR
Form R6-7100-57 (9/66)	N-9	0-885	Ralph P. Thompson MAY 13, 1960 RALPH P. THOMPSON