## **OREGON CORNER RESTORATION FORM**

COUNTY: Umatilla DATE: 01/19/06

CORNER DESIGNATION: 3N31, Z-7, The South One-Quarter Corner of Section 32.

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by Josiah A. Burnett, under Contract No. 92, dated September 12, 1860. Record states: Set a post for 1/4 Sec. corner, drove charred stake and raised mound with trench, as per instructions. Willard Bradley, in Survey recorded at Book 2, Page 405, recovered the original GLO corner and set a large stone with glass and old stake under. Bradley notes a fence runs North from the corner. Survey No. 05-111-C holds centerline of East-West road and field line North as position for this corner.

MONUMENT AND ACCESSORIES FOUND: Held intersection of field berm North and South, and centerline of Fansier gravel County Road East and West, as best remaining evidence of original corner, and Willard Bradleys perpetuation of that original corner.

## MONUMENT MARKING DETAIL:

T3N R31E <u>1 S32</u> 4 S5 T2N 2006 PLS 1106

## MONUMENT SET:

At reestablished corner position, set a 1 1/4" x 30" galvanized iron pipe with a 2 3/8" brass cap with cap 10" below road surface. Marked as shown in Monument Marking Detail. A silver Deep 1 magnet buried 20" in ground bears North 32° East, 45.0 feet. The top of a old power pole guy anchor buried 8" below ground bears South 02° West, 22.8 feet. A 5/8" x 24" iron rebar with yellow plastic cap stamped "OR PLS 1106, WA PLS 17372", bears South 83° West, 78.7 feet. Set steel fence post with witness sign by this accessory. An orange Deep 1 magnet buried 20" in the ground bears North 24° West, 47.3 feet. Attached bearing object signs to rebar accessories and guy anchor. Buried bearing object signs with magnets.

LOCATION AND COMMENTS:

Corner at intersection of Fansier County Road and field berm North and South.

OREGON STATE PLANE COORDINATE, North Zone, NAD 83(91), International Feet: N = 741370.34 E = 8594497.79

FIRM: William R. Wells, PLS P.O. Box 1696 Pendleton, OR 97801

COMPASS DECLINATION: 18° East

Witnesses: Jason Wells, LSIT

/3N31Z7

## Surveyor's Seal



N/2-462-C