OREGON CORNER RESTORATION FORM

Section 10 Township 4N Range 37E

County Umatilla Date 6/08/94

CORNER DESIGNATION: L-13

Previous Renewals/Surveys, etc.

Corner originally established by U.S. Deputy Surveyor George S.Pershin under GLO contract No. 332 dated July 29,1879. The Surveyor General records state: Set basalt stone 20"x 10"x 10" on a spur extending North for 1/4 sec. cor., from which: A pine 30" ins. diam. brs. N 63° E, 156 lks. dist. A pine 5 ins. diam. brs. N 54° W, 13 lks. dist.

Monument(s) & Accessories Found: (Condition and Source) Found a basalt stone 20"x 14"x 10" firmly set and marked 1/4 on the west face. A 8" pine stump with visible scribes laying on top of the ground bears N 48° W, 10.7 feet (record states 13 1ks). A pine stump with axe marks visible at the bottom of a blaze bears N 63° E, 103.0 feet (156 lks).

Monument	Detail		R37E 4	
		S16	S15	
		7.00 million (1975)	1994 PLS 1106	
	- e - 1183			

Monument Set (Procedures and Description): At position of recovered corner stone, set a 2 1/2" brass cap on a 1 1/2" x 30" galvanized iron pipe 20" in the ground with a surrounding mound of earth and stone. Brass cap marked as shown above. Corner stone was placed in the new earth and stone mound.

New Accessories:

A 15" ponderosa pine bears N 78 $1/2^{\circ}$ E, 65.9 ft. and is scribed 1/4 S15 BT. A 15" ponderosa pine bears S 5 $1/2^{\circ}$ W, 30.5 ft. and is scribed 1/4 S16 BT. A 6" ponderosa pine bears N 88° W, 43.1 ft. and is scribed 1/4 S16 BT. A 13" ponderosa pine bears N 3 $1/2^{\circ}$ E, 54.6 ft. and is scribed 1/4 S15 BT. Bearing trees have a brass washer stamped PLS 1106 nailed to face of blaze. Attached bearing object and witness signs to each tree. Painted a 6" band and face of blaze red. Set a steel fence post 4 feet North of the monument with attached witness corner sign.

Location & Comments: Corner is located on a open North facing spur, 75' N. of a old logging road.

Compass Declination: 18° E

Surveyor's Seal REGISTERED

ull R. Well

OREGON

JULY 22, 1977

WILLIAM R. WELLS

1106

renews 6/3c/96

Firm/agency: Tomkins-Wells Joint Venture PROFESSIONAL Land Surveying LAND SURVEYOR P.O. Box 1696 Pendleton, Oregon 97801 Party Chief: Greg Flowers Notes: Greg Flowers

Witness: Todd Rosenbalm

Umatilla County Surveyor Date Red d By

RECEIVED BY