ERTIFIED RECORD OF LAND CORNER MONUMENTATION

T 4N , R 37E . , W.M.

History of original corner establishment:

This corner was originally established by Seorge S. Pershin, U.S. Deputy, under contract No. 322, dated July 29, 1879. The originally notes state:

Set fir post on N.E. hillside at head of ravine for corner to Sections 25, 26, 35, and 36 from which:

spruce 28 in diam. bears N 42°E, 28 lks dist. fir 7 in diam. bears S 50°E, 33 lks dist. spruce 8 in diam. bears 8 40°M, 21 lks dist. spruce 12 in diam. bears N 65°M, 24 lks dist.

DIAGRAM T4N R37E S26 S25 S35 S36 1991 PLS 1106

Corner No. Compass Declination: 18.0°

Description of corner evidence found:

Found axle with a 3" top on a 1 1/4" by 32" long shaft on West side of an old road, and along an old existing West fence line.

Description of monument and accessories I established to perpetuate the original location of this corner:

The origin of the axle shaft is not known, but it has been used on all surveys in the area. I accept the axle shaft as a perpetuation of the original corner monument.

At the position of the center of the axel shaft, set a 2 1/2" brass cap on a 1 1/4" by 30" galvanized iron pipe 24" in ground, and surrounded with a mound of earth and stone. Buried axel horizontally on the West side of new monument.

Marked 4 new bearing trees:

A 12" Englemann spruce bears N 71 1/2°E, 29.2', scribed T4N R37E S25 BT. A 18" white fir bears N 41°W, 12.1', scribed T4N R37E S26 BT. A 15" white fir bears S 55°E, 52.5', scribed T4N R37E S36 BT. No close trees to the SW. A 8" white fir bears N 90°E, 51.3', scribed T4N R37E S25 BT.

Placed bearing object signs on all new bearing trees.

Set steel fence post West of corner with a witness corner sign attached.



Unice or	County of
	hereby certify that the within instrument was filed in this office
for record on the day of	
	by

(COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

Office of

1

RECEIVED BY

(DEPUTY)

Umatilla County Surveyor Date Rec'd By No

\$ GPO-798-276