Index	CORNER OFFICER (OFFICER)
File No.	CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No No
T <u>45</u> R. <u>30E</u>	_R.DCountyUmatilla
Merid. <u>Willamette</u>	N.F. Umatilla Stote Oregon
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
T45 R30E	Found old mound of stone 15 ft. North of old E-W
4 510 511	fence line. Found rotten wood in hole in center of
<u> </u>	the mound.
S15 S14	
Ņ 1981	
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
PLS 848	
· •	No bearing trees originally established.
	Since evidence found is harmonious with found corners
PHOTO IDENTIFICATION DATA	61 1/4 Wit. DOUTH AND 1/2 Mi. Fast the coets as the
	mound (in the hole) is accepted as the corner
Photo No.	position.
Filed At	-
Ident. By	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
Signature	Corner is on a SW slope in open ground, 380 ft.
PLANE COORDINATE POSITION DATA	North of Oraw Dottom. A road, coursion NW is
State Zone	approx. 700 ft. South of corner.
X	•
Y	
Estab. By	
Agency	8
Signature	Title Division Headquarters Date 7100-52-(3,68)
	PL5 848 Mt. Vernon, DR 8/4/81 5

.....

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set $3" \times 30"$ GALV. iron pipe with 3" brass cap stamped as shown in the diagram, set 16" in the ground and raised a mound of stone around the pipe.

From which:

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A juniper 8 in. dia. bears 562°E, 116.8 ft. scribed T45, R30E, 514 BT. A pine 14" dia. bears 558°W, 146.3 ft. scribed T4S, R3OE, S15 BT.

No other trees available. Set steel post with warning sign 7 ft. North from corner.

Nailed bearing tree signs and brass washers stamped PLS 848 to trees.

Painted a red band around each tree.

_		<u> </u>						10
	Work Done By D.M. Fergu	JSON_Title_	Surveyor	Dote	4/81Stet	e Registration No. gency	OR PLS 84	<u> </u>
_	CertifieREGISETEREPoored	Yes X No	Filed At: Umat	illa Co.	Surv.	Office Date	10/81	11
	PROFESSIONAL LAND SURVEYOR		REMARK					
4	OREGON JULY 12, 1968 DOUGLAS M. FERGUSON 8 4 8							

Index File No.

R.

Tract or Surv. No.

Cor.

Index File No	CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No. No. R.D County
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
SEC.	BLM loc. poster on iron fence post in 4' x 4' x 2½' mound of stone pointed rod. Loc. poster says approx. cor.
120	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
PHOTO IDENTIFICATION DATA	
Photo No	-
Object Ident.	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
Ident. By Signature	
PLANE COORDINATE POSITION DAT	A T
State Zone X Y	_ _ _
Estab. By	
B.Signature B.Signature	Eng Tech/ Division Headquarters 4/78 7100-52 (3/68)

The second secon	CORNER R	ECORD (PERPE	TUATION)	GPO 902-67
MONUMENT : DESCRIBE NEW MONU	MENT SET, OR WORK DONE TO	PRESERVE EXISTIN	NG MONUMENT	***
	•			
				g
,				
				10
Work Done By	Title	Date	State Registration No.	10
Work Done By		Date	State Registration No. or Agency	

____!

Index File No.

T.

R.

M.

Tract or Surv. No.

Cor.

13