USDA-FOREST SERVICE		
Index File No. M-19	CORNER RECORD (SEARCH) Tract or (Ref. FSM 7151.4) Survey No	Cor. No.
T 45 R 30E	_R.D. <u>Ukiah</u> County Umatilla	
Merid. <u>Willamette</u>	N.F. Dinatilla Stote Drenon	
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND	
T4S R3DE	Corner not previously established.	
S 1/16 S 14		•
T C	DESCRIPE REARING TORSE OF OTHER OFFICE	2
1981	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND N/A	
PLS 848		
PHOTO IDENTIFICATION DATA		
Photo No.		
Filed At.		
Object Ident	DESCRIBE CORNER LOCATION RELATIVE TO MEAD ON SECTION	3
ident. By	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO H	OW TO REACH CORNER
Signature	Corner is at the edge of the timber or	յ the South ´
PLANE COORDINATE POSITION DATA	Otop of all open flong. Anorov Ano ft	C
StateZone	a road which runs down the top of that	ridge.
X		
Υ		<b>K</b>
Estab. By		· · · · · · · · · · · · · · · · · · ·
Signature	Title Division Headquarters Date	4
ray Mfar	PIS 8//8	7100-52 (3, 68)
	PLS 848 Mt. Vernon, DR 8/12	<u>/81</u>

## CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set 3"x30" galv. iron pipe with 3" brass cap stamped as shown on the diagram, set 12 inches in the ground and raised a mound of stone around the pipe.

From which:

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A pine 14 in. dia. bears West 30.8 ft. scribed CS 1/16 S 14 BT. A pine 18" dia. bears 552°E, 87.2 ft. scribed CS 1/16 S 14 BT. Set steel post with warning and boundary signs 5 ft. West and 5 ft. East from the corner. Nailed bearing tree signs and brass washers stamped PLS 848 to trees. Painted red band around each tree.

Work Done By D.M. Ferguson title Surveyor Dote Or Agency Or Agency

Index File No.

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON

Tract or Surv. No.

Mike Woodward

Cor.

13