


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by Rufus S. Moore under General Land Office Contract No. 451. Surveyor General Records state:

Set basalt stone 15 X 15 X 15 ins. for cor. to Tps 4 and 5 S Rgs 33 1/2 E and 34 E.



No record of subsequent remonumentation was found in county records.


Description of corner evidence found:

Found stone 18" X 16" X 15", faint marks.

(See map of Survey, dated December, 1975)

Description of monument and accessories established to perpetuate the original location of this corner

In corner position I set 2 1/2" X 30" iron pipe with brass cap marked as shown 16" in ground.
 There are no trees or bearing objects within 1000 ft. of cor.
 Buried stone North and along side pipe.
 Raised mound of stone 7 ft. X 5 ft. X 3 ft. high.
 Set steel fence posts 5+ West and North.



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Duane I. Griffith
OREGON
JULY 10, 1954
DUANE I. GRIFFITH
644

Brass Washer nailed to BT blazes.
 Used steel tape and magnetic compass with 19° 30' East declination.
 Measured to center of all BTs.

Office of..... County of.....
 State of....., I hereby certify that the within Instrument was filed in this office for record on the day of.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

2-25