

USDA-FOREST SERVICE

Index File No. F-9

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)


Tract or Survey No. _____ Cor. No. _____

T 5N R. 38E R.D. W² County UMATILLA

Merid. WILL N.F. UMATILLA State OREGON

CORNER DIAGRAM

DESCRIBE CORNER MONUMENT FOUND



DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. _____
Filed At. _____
Object Ident. _____
Ident. By _____
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____
Agency

Signature S/ HOWARD L PERRY Title _____ Division PLS 1294 Headquarters _____ Date 9/80 7100-52-(3.68)

CORNER RECORD (PERPETUATION)

- Description of monument and accessories | established to perpetuate the original location of this corner:

At surveyed point, set 1"x30" Galvanized Pipe with 3" brass cap stamped:

Set pipe 24" in ground. No stones available for rock mound.

Bearing Trees:

A White Fir 11" dia. bears N88⁰W, 79.8 ft., scribed: N 1/16 S8 BT.

A White Fir 15" dia. bears S37⁰W 58.3 ft., scribed: N 1/16 S8 BT.

- Attached 54-3 and 54-4 signs to both BTs. Attached brass washers stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs red.

CROWN ZELLER BACH

T5N R38E

N $\frac{1}{16}$

S8

1980

OR PLS 129A

REMARKS

Index File No.

F-9

T.

5N

R.

38E

M.

Tract or Surv. No

Cor.

12

11