


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-7

History of original corner establishment:

No corner was originally set.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 1"x30" Galvanized Pipe with 3" brass cap stamped:



Set pipe 24" in ground with mound of dirt to cap.

From which:

A White Fir 14" dia. bears N76°E 24.3 ft., scribed:  
C 1/4 S8 BT.

A Spruce 13" dia. bears N41°W 57.9 ft., scribed:  
C 1/4 S8 BT.

Attached 54-3 and 54-4 signs to both BTs. Attached brass washers stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs red.



I hereby certify the above corner monument was established as herein described on November 4, 1980.

Witnesses: R. Orton  
G. Wagoner  
M. Wagoner

Office of.....County Surveyor..... County of.....Umatilla.....  
 Oregon  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the.....day of.....*December*....., 19*80*  
 ..*David H. Rasmussen* by ..*Betty Sheth*.....  
 (COUNTY OFFICIAL) (DEPUTY)