Index File No. G-8	CORNER RECORD (SEARCI	H) Tract or Survey No	Cor. ;
T 5N R. 38E		UMATILLA	
Merid. WILL	N.F. UMATILLA State		
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND		
A TEN DOOF			
T5N R38E			
_ 1		•	
h $\frac{1}{16}$			•
C	DESCRIBE BEARING TREES OR OTHER O	FEICIAL ACCESSORIES FOUN	0
s 8		· · · · · · · · · · · · · · · · · · ·	
1	i i		
•			
	6		
PHOTO IDENTIFICATION DATA	7		
Photo No.	1		
Filed At.	-		
Object Ident	DESCRIBE CORNER LOCATION RELATIVE	TO NEAD-BY SEATURES ALE	0 HOW TO DEADY CORNER
ident. By	- Sesemble Connent Cooki low RECKITIVE	TO WEAR-BY FEATURES, ALS	O HOW TO REACH CORNER
Signature	7		
PLANE COORDINATE POSITION DATA	<u>~</u>		
State Zone	·		
X	- i		
^	-		•
V	- ∤		
Y			
Estab. By			

CORNER RECORD (PERPETUATION)	
"Description of monument and accessories I established to perpetuate the	:
original location of this corner:	
At surveyed point set 1"x30" Galvanized Pipe with 3" brass cap stamped:	CROWN ZELLERSAN
Set pipe 22" in ground with mound of stone and dirt to cap.	$\begin{array}{ccc} & \text{T5N} & \text{R38E} \\ & \text{E} & \frac{1}{16} \end{array}$
New BTs:	C
A_Spruce_11"_diabears_N22 ⁰ E, 27.4°ft., scribed_ CE 1/16 S8 BT.	S 8 : - 1980 PLS 1294 :
A Fir 6" dia. bears S49 ^o E, 15.0 ft., scribed CE 1/16 S8 BT.	
Attached 54-3 and 54-4 signs to both BTs. Attached brass washer stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs red.	
Work Done By Title	Date
Certified Cor. Record Preserted 7 (Ves.) No. Filed At:	

M.

Tract or

Cor.

Index File No. T. R. G-8 5N 38E